

## Suzuki GSX-S750 2015- (ARA-1 + ARA-K4B)

Secure the bike on a stand.




Remove the seats and the side covers.

Remove the fuel tank and the airbox.



Use the following connections without  
the iQSE:

Plug the ARA connectors in-line with the  
ignition coil connectors.





# Advanced Rider Assistant Supplementary Manual




## Suzuki GSX-S750 2015- (ARA-1 + ARA-K4B)

Use the following connections with the iQSE:


Connect the QSX connectors to the ignition coil connectors.

Plug the ARA connectors in-line with the QSX free connector and the bike harness plug.

*(Bike harness plug -> ARA plugs -> QSX plugs -> ignition coil plug.)*



Connect the ARA Black wire terminal to the battery negative terminal.



Optional:

Connect the Pink ARA wire to the Black/Yellow wire of the Clutch switch at the Transparent multi connector.

*(While the connector is connected, turn ignition on. Measure the voltage (DC 20V setting) on the wires, at the back side of the plug. You need to use the wire where the voltage value changes while you pull the clutch lever. Alternatively check the clutch switch indication in the ARA application on your phone.)*





# Advanced Rider Assistant Supplementary Manual




## Suzuki GSX-S750 2015- (ARA-1 + ARA-K4B)


Locate the ABS connector under the fuel tank.



Splice the ARA Green wire to the White/Yellow wire of the ABS connector.



Splice the ARA Blue wire to the White/Red wire of the ABS connector.



# Advanced Rider Assistant Supplementary Manual



## Suzuki GSX-S750 2015- (ARA-1 + ARA-K4B)

Mount the switch onto the handlebar.



Mount the LED indicator.



Typical position for the ARA module.

Secure the unit properly.

