



**SUPPLEMENTARY MANUAL**  
for GIPRO-K03

REMOVE THE MAIN SEAT.  
REMOVE THE LEFT AND RIGHT SIDE  
COVERS UNDER MAIN SEAT AND  
FUEL TANK.  
REMOVE THE PLASTIC COVER  
IN FRONT OF FUEL TANK.  
LIFT UP OR REMOVE  
THE FUEL TANK.



LOCATE THE GPS  
(GEAR POSITION SENSOR)  
COUPLER.  
(GREEN, 4-POLE CONNECTOR  
AT LEFT SIDE BELOW MIDDLE FAIRING)



RELEASE AND REMOVE  
THE GREEN/RED AND BLACK WIRES  
FROM FEMALE CONNECTOR.  
(GREEN, 4-POLE CONNECTOR  
AT LEFT SIDE BELOW MIDDLE FAIRING)




# Kawasaki 1400GTR

2008-2013




INSERT THE TWO FEMALE METAL CONTACTS INTO THE SMALLER 3-POLE TRIANGULAR PLUG THROUGH THE BACK UNTIL THEY CLICK INTO PLACE.



RELEASE AND REMOVE THE GREEN/RED AND BLACK/YELLOW WIRES FROM MALE CONNECTOR.  
(GREEN, 4-POLE CONNECTOR AT LEFT SIDE BELOW MIDDLE FAIRING)



INSERT THE TWO MALE METAL CONTACTS INTO THE LARGER 3-POLE TRIANGULAR PLUG THROUGH THE BACK UNTIL THEY CLICK INTO PLACE.



# Kawasaki 1400GTR

2008-2013



**PLUG ATRE CONNECTORS IN-LINE  
WITH THE TWO CONNECTORS.**  
(WHITE, 3-POLE TRIANGULAR CONNECTORS)



**CONNECT ATRE RED WIRE TO  
BROWN WIRE OF  
REAR BRAKE LIGHT SWITCH  
CONNECTOR.**  
(TRANSPARENT, 2-POLE CONNECTOR  
UNDER MAIN SEAT AT RIGHT SIDE)



**TYPICAL POSITION FOR THE  
GEAR INDICATOR.**  
(TRE MODE: 4)

